national diagnostics

Conforms to regulation (EC) no. EU 453/2010

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name: Ecoscint XR

Product Number: LS-272

1.2 Relevant Identified Uses of the Substance/Mixture and Uses Advised Against Investigational research by professional users

1.3 Details of the Supplier of the Safety Data Sheet

Manufacturer National Diagnostics 305 Patton Drive Atlanta, GA 30036 (404) 699-2121 (800) 526-3867 info@nationaldiagnostics.com

1.4 Emergency Telephone Number

ChemTel Inc.

Contract number MIS8894340 1-800 255-3924 (United States, Canada, Puerto Rico & US Virgin Islands) 01-800-099-0731 (Mexico) 400-120-0751 (China) 000-800-100-4086 (India) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) +1-813-255-3924 (All other regions)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS/CLP]

- H302 Acute Toxicity-Oral (Category 4)
- H305 Aspiration Hazard (Category 2)
- H315 Skin Corrosion/Irritation (Category 2)
- H319 Serious Eye Damage/Eye Irritation (Category 2A)
- H411 Chronic Hazards to the Aquatic Environment (Category 2)

2.2 Label Elements GHS LABEL ELEMENTS AND CLASSIFICATION

GHS Label Elements



WARNING

H302 - Harmful if swallowed H305 - May be harmful if swallowed and enters airways. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.

P262 - Do not get into eyes, on skin or on clothing.

P273 - Avoid release to the environment.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Call a POISON CENTER or

doctor/physician.

P337+P313 - IF eye irritation persists: Get medical advice/attention.

2.3 Other Hazards

None found.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixture

Chemical Names/Description

Blend of scintillators in chiral phenylalkanes.

Component List

Component	% Comp.	CAS#	EC #	Classification
Phenyl Xylyl Ethane (PXE)	50 - 70	6196-95-8	228-249-2	H304, H315, H319
Primary Alcohol Ethoxylate	5 - 10	68439-46-3	614-482-0	H318
Linear alkyl phenyl ethoxylates	20 - 30	9016-45-9	500-024-6	H315, H319, H411
Butoxy Ethanol	5 - 10	111-76-2	203-905-0	H302, H312, H315, H319, H332

4070/0000

SECTION 4 - FIRST AID MEASURES

4.1 Description of First Aid Measures

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion

DO NOT INDUCE VOMITING. If swallowed and the person is conscious, immediately give large amounts of water. Get medical attention.

Skin

Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes

Immediately flush eyes with plenty of water for at least fifteen minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Inhalation

Phenyl Xylyl Ethane (PXE):

Sore throat, coughing, labored breathing, sneezing and burning sensation, depending on the concentration and duration of exposure. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure.

Primary Alcohol Ethoxylate:

Sore throat, coughing, labored breathing, sneezing and burning sensation, depending on the concentration and duration of exposure. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure.

Linear alkyl phenyl ethoxylates:

Discomfort in nose and throat, nasal discharge, coughing, difficulty breathing.

Butoxy Ethanol:

Burning in nose and throat, coughing. Headache, dizziness, drowsiness, fatigue, nausea.

Ingestion

Phenyl Xylyl Ethane (PXE):

Salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under Inhalation.

Primary Alcohol Ethoxylate:

Salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under "Inhalation."

Linear alkyl phenyl ethoxylates:

Abdominal discomfort, nausea, and diarrhea.

Butoxy Ethanol:

Headache, dizziness, drowsiness, fatigue, nausea, vomiting.

Skin

Phenyl Xylyl Ethane (PXE):

Drying, reddening, itching, and cracking. Repeated or prolonged contact with large amounts of this material may result in absorption through the skin to produce toxic effects.

Primary Alcohol Ethoxylate:

Drying, reddening, itching, and cracking. Repeated or prolonged contact with large amounts of this material may result in absorption through the skin to produce toxic effects.

Linear alkyl phenyl ethoxylates:

Local redness and swelling.

Butoxy Ethanol:

Redness, pain and itching.

Eyes

Phenyl Xylyl Ethane (PXE): Redness, tearing, and blurred vision.

Primary Alcohol Ethoxylate:

Redness, tearing, and blurred vision.

Linear alkyl phenyl ethoxylates:

Excess blinking and tear production. Marked redness and swelling of the eye with injury to the cornea.

Butoxy Ethanol:

Redness, tearing, and pain.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Unknown/not applicable

SECTION 5 - FIRE FIGHTING MEASURES

5.1 Extinguishing media

Water spray, dry chemical, alcohol-resistant foam, or carbon dioxide.

5.2 Special Hazards Arising from the Substance/Mixture

Hazardous Combustion Products

Thermal decomposition products may include carbon monoxide, carbon dioxide, and hydrocarbons.

Hazardous Decomposition Products

Combustion may produce toxic oxides of carbon and reactive hydrocarbons.

Hazardous Polymerization

Will not occur under normal conditions of use (See Sections 10.4 & 10.5).

5.3 Advice for Firefighters

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

5.4 Further Information

No data available.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions

Wear appropriate protective equipment as specified in Section 8.

6.2 Environmental Precautions

Prevent discharge into the environment. Dike spills and stop leakage where practical. Do not allow material to enter drains.

6.3 Methods and Materials for Containment and Cleaning Up

Eliminate source of ignition. Ventilate area. Cover with absorbent material (soda ash) to confine spill and sweep or shovel into container. Close container tightly. Avoid breathing vapors.

6.4 References to Other Sections

For disposal information, see Section 13. For protective clothing and equipment, see Section 8.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Avoid contact and inhalation. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling. Transfer methods should avoid static sparks. Do not eat, drink, or smoke in areas of use or storage.

7.2 Conditions for Safe Storage (including any incompatibles)

Keep in tightly closed container, stored in a cool, dry, ventilated area away from sources of heat or ignition. Protect from physical damage.

Incompatibles

Phenyl Xylyl Ethane (PXE): Oxidizing agents.

Primary Alcohol Ethoxylate:

Strong oxidizing agents. Aluminum surfaces at temperatures above 120 degrees..

Linear alkyl phenyl ethoxylates: Oxidizing agents.

Butoxy Ethanol:

Strong oxidizing agents. Strong bases and salts of strong bases at elevated temperatures. Aluminum surfaces.

7.3 Specific End Uses

Investigational research by professional users

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PRECAUTIONS

8.1 Control Parameters

Component: Phenyl Xylyl Ethane (PXE) ACGIH Threshold Limit Value (TLV): none established OSHA Permissable Exposure Limit (PEL): None established

Component: Primary Alcohol Ethoxylate

ACGIH Threshold Limit Value (TLV): none established OSHA Permissable Exposure Limit (PEL): None established

Component: Linear alkyl phenyl ethoxylates ACGIH Threshold Limit Value (TLV): none established OSHA Permissable Exposure Limit (PEL): None established

Component: Butoxy Ethanol ACGIH Threshold Limit Value (TLV): 25 ppm (skin) OSHA Permissable Exposure Limit (PEL): 25 ppm

8.2 Exposure Controls

Engineering Controls

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source.

Respiratory Protection

For conditions of use where exposure to the substance is apparent, consult an industrial hygienist. For emergencies, or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator.

Eye Protection

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Skin Protection

Wear protective gloves and clean body covering clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical & Chemical Properties

a. Appearance	Clear solution	b. Odor	Odorless
c. Odor Threshold	N.A.	d. pH	N.A.
e. Melting/Freezing Point (^o C)	0	f. Boiling point (^o C)	302-318
g. Flash Point (^o C)	91	h. Evaporation Rate	Not measureable
i. Flammability	N.A.	j. Upper/Lower Flammability or Explosive Limits	ND
k. Vapor Pressure	< 0.1	I. Vapor Density (Air = 1)	Not determinable
m. Relative Density	0.91	n. Water Solubility	Slightly soluble.
o. Partition Coefficient n-octanol/water	Mixture	p. Autoignition Temperature (°C)	>375
q. Decomposition Temperature (^o C)	N.A.	r. Viscosity	ND
s. Explosive Properties	Can be made to burn	t. Oxidizing Properties	N.A.

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Material can be made to burn; combustion is generally not self-sustaining. Reacts with oxidizers.

10.2 Chemical Stability

Stable under normal conditions of use (See sections 10.4 & 10.5).

10.3 Possibility of Hazardous Reactions

Will not occur under normal conditions of use (See Sections 10.4 & 10.5).

10.4 Conditions to Avoid

Heat, sources of ignition.

10.5 Incompatible Materials

Phenyl Xylyl Ethane (PXE): Oxidizing agents.

Primary Alcohol Ethoxylate:

Strong oxidizing agents. Aluminum surfaces at temperatures above 120 degrees..

Linear alkyl phenyl ethoxylates: Oxidizing agents.

Butoxy Ethanol:

Strong oxidizing agents. Strong bases and salts of strong bases at elevated temperatures. Aluminum surfaces.

10.6 Hazardous Decomposition Products

Combustion may produce toxic oxides of carbon and reactive hydrocarbons.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product LD50 Values

Oral Rat LD50 (mg/kg) > 1500

Dermal Rabbit LD50 (mg/kg)

No Data

Component Cancer List Status

	NTP Carcinogen			
Phenyl Xylyl Ethane (PXE)	Known	Anticipated	IARC Category None	
	No	No		
Primary Alcohol Ethoxylate	No	No	None	
Linear alkyl phenyl ethoxylates	No	No	None	
Butoxy Ethanol	No	No	None	

Potential Health Effects

Inhalation

Phenyl Xylyl Ethane (PXE)

Breathing of the mists, vapors or fumes may irritate the nose, throat and lungs.

Primary Alcohol Ethoxylate

Information not found.

Linear alkyl phenyl ethoxylates

Vapors or mist, expecially as generated from heating the material or as from exposure in poorly ventilated areas or confined spaces, may be irritating and cause discomfort in nose and throat. Prolonged exposure may cause difficulty breathing.

Butoxy Ethanol

Vapors may cause irritation to the nose, throat, and respiratory tract and are toxic if inhaled.

Ingestion

Phenyl Xylyl Ethane (PXE)

May cause irritation of the mouth, throat, and gastrointestinal tract. Exposure may also cause central nervous system symptoms.

Primary Alcohol Ethoxylate

Moderately toxic by ingestion.

Linear alkyl phenyl ethoxylates

May be harmful by ingestion.

Butoxy Ethanol

Moderately toxic if ingested.

Skin

Phenyl Xylyl Ethane (PXE)

May cause skin irritation.

Primary Alcohol Ethoxylate

Severely irritating to the skin and moderately toxic if absorbed through the skin.

Linear alkyl phenyl ethoxylates

Brief contact may cause slight irritation. Prolonged contact, as with clothing wetted with material, may cause more severe irritation and discomfort.

Butoxy Ethanol

Product is mildly irritating to the skin and toxic if absorbed through the skin.

Eyes

Phenyl Xylyl Ethane (PXE)

Exposure to vapors, fumes or mists may cause irritation. Direct contact may cause irritation.

Primary Alcohol Ethoxylate Severely irritating to the eyes.

Linear alkyl phenyl ethoxylates

Causes irritation and possible injury to the cornea.

Butoxy Ethanol

Causes severe eye irritation.

Carcinogenicity

Phenyl Xylyl Ethane (PXE) Not listed by NTP or IARC as a known or possible carcinogen.

Primary Alcohol Ethoxylate No information available.

Linear alkyl phenyl ethoxylates Not listed by NTP or IARC as a known or possible carcinogen.

Butoxy Ethanol

Not listed as a known or anticipated carcinogen by NTP or IARC.

Mutagenicity

Phenyl Xylyl Ethane (PXE) No information available.

Primary Alcohol Ethoxylate No information available.

Linear alkyl phenyl ethoxylates No information available.

Butoxy Ethanol No information found.

Reproductive Toxicity

Phenyl Xylyl Ethane (PXE) No information available.

Primary Alcohol Ethoxylate No information available.

Linear alkyl phenyl ethoxylates No information available.

Butoxy Ethanol

Inhalation exposure of pregnant rabbits caused some lethality to the dam and fetus at 200 ppm, but there were no effects at 100 ppm and below. Inhalation exposure to pregnant rats caused irritancy to the dams and related fetotoxicity at 200 and 100 ppm, but there were no effects at 50 ppm and below.

Teratogenic Effects

Phenyl Xylyl Ethane (PXE) No information available.

Primary Alcohol Ethoxylate No information available.

Linear alkyl phenyl ethoxylates

No information available.

Butoxy Ethanol

Has not been shown to cause birth defects.

Routes of Entry

Phenyl Xylyl Ethane (PXE) Ingestion, inhalation, skin contact.

Primary Alcohol Ethoxylate Inhalation, ingestion, skin contact. Linear alkyl phenyl ethoxylates Ingestion, inhalation.

Butoxy Ethanol

Inhalation, ingestion, skin contact.

Target Organ Statement Phenyl Xylyl Ethane (PXE)

No information available.

Primary Alcohol Ethoxylate

No information available.

Linear alkyl phenyl ethoxylates

No information available.

Butoxy Ethanol

Preexisting skin, eye, and lung disorders may be aggravated by exposure.

SECTION 12 - ECOLOGICAL INFOMATION

12.1 Toxicity

COMPONENT: Phenyl Xylyl Ethane (PXE)

	Vertebrates	Invertebrates	Algae	Microorganisms	
Aquatic Toxicity (ppm unless otherwise noted)	No data	No data	No data	No data	
	Birds	Arthropods	Plants	Microorganisms	
Terrestrial Environment Toxicity (ppm unless otherwise noted)	No data	No data	No data	No data	
COMPONENT: Primary Alcohol Etho	oxylate Vertebrates	Invertebrates	Algae	Microorganisms	
Aquatic Toxicity (ppm unless otherwise noted)	No data	No data	No data	No data	
	Birds	Arthropods	Plants	Microorganisms	
Terrestrial Environment Toxicity (ppm unless otherwise noted)	No data	No data	No data	No data	
COMPONENT: Linear alkyl phenyl ei	thoxylates Vertebrates	Invertebrates	Algae	Microorganisms	
COMPONENT: Linear alkyl phenyl en Aquatic Toxicity (ppm unless otherwise noted)			Algae EC50 (48hrs) 20 mg/L	Microorganisms No data	
Aquatic Toxicity	Vertebrates	LC50(48hrs, daphnia)		•	
Aquatic Toxicity (ppm unless otherwise noted) Terrestrial Environment Toxicity	Vertebrates No data	LC50(48hrs, daphnia) 1.821 mg/L	EC50 (48hrs) 20 mg/L	No data	
Aquatic Toxicity	Vertebrates No data Birds	LC50(48hrs, daphnia) 1.821 mg/L Arthropods	EC50 (48hrs) 20 mg/L Plants	No data Microorganisms	
Aquatic Toxicity (ppm unless otherwise noted) Terrestrial Environment Toxicity (ppm unless otherwise noted)	Vertebrates No data Birds	LC50(48hrs, daphnia) 1.821 mg/L Arthropods	EC50 (48hrs) 20 mg/L Plants	No data Microorganisms No data Microorganisms	
Aquatic Toxicity (ppm unless otherwise noted) Terrestrial Environment Toxicity (ppm unless otherwise noted)	Vertebrates No data Birds No data	LC50(48hrs, daphnia) 1.821 mg/L Arthropods No data	EC50 (48hrs) 20 mg/L Plants No data	No data Microorganisms No data	
Aquatic Toxicity (ppm unless otherwise noted) Terrestrial Environment Toxicity (ppm unless otherwise noted) COMPONENT: Butoxy Ethanol Aquatic Toxicity	Vertebrates No data Birds No data Vertebrates LC50 (96hr, trout)	LC50(48hrs, daphnia) 1.821 mg/L Arthropods No data Invertebrates EC50 (48 hr daphnia)	EC50 (48hrs) 20 mg/L Plants No data Algae	No data <u>Microorganisms</u> No data <u>Microorganisms</u> Toxicity Threshold	

12.2 Persistence and Degradability

Phenyl Xylyl Ethane (PXE) No data

Primary Alcohol Ethoxylate No data

Linear alkyl phenyl ethoxylates

Readily biodegradable >97% elimination in 30 days

Butoxy Ethanol Readily biodegradable (90% in 28 days)

12.3 Bioaccumulative Potential

Phenyl Xylyl Ethane (PXE) No data

Primary Alcohol Ethoxylate No data

Linear alkyl phenyl ethoxylates No data

Butoxy Ethanol No data

12.4 Mobility in Soil

Phenyl Xylyl Ethane (PXE) No data

Primary Alcohol Ethoxylate No data

Linear alkyl phenyl ethoxylates No data

Butoxy Ethanol No data

12.5 Results of PBT and vPvB Assessment

Phenyl Xylyl Ethane (PXE) No data

Primary Alcohol Ethoxylate No data

Linear alkyl phenyl ethoxylates Substance is PBT / vPvB

Butoxy Ethanol Not PBT/vPvB

12.6 Other Adverse Effects

Phenyl Xylyl Ethane (PXE) None

Primary Alcohol Ethoxylate None

Linear alkyl phenyl ethoxylates None

Butoxy Ethanol None

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Offer surplus or non-recyclable product to licensed disposal company. Disposal is subject to user compliance with applicable law and product characteristics at time of disposal. Dispose of packaging as product.

SECTION 14 - TRANSPORT INFORMATION

	ADR/RID	ΙΑΤΑ	IMO	DOT
14.1 UN Number	UN3082	N.A.	UN3082	N.A.
14.2 Shipping Name	Environmentally Hazardous Substance Liquid, N.O.S.	Not regulated.	Environmentally Hazardous Substance, Liquid, N.O.S.	Not regulated.
14.3 Hazard Class	9	N.A.	9	N.A.
14.4 Packing Group	III	N.A.	111	N.A.
14.5 Environmental Hazards	N.A.	N.A.	Marine pollutant	N.A.
14.6 Special Precautions	N.A.	N.A.	N.A.	N.A.

SECTION 15 - REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance/Mixture United States

TSCA Regulatory Statement

All intentional ingredients are listed on the TSCA Inventory.

SARA 311/312 Hazard Categories

Component	Fire	Pressure	Reactivity	Acute	Chronic

Phenyl Xylyl Ethane (PXE)	No	No	No	Yes	No
Primary Alcohol Ethoxylate	No	No	No	Yes	No
Linear alkyl phenyl ethoxylates	No	No	No	Yes	No
Butoxy Ethanol	Yes	No	No	Yes	No

Europe

EEC Regulatory

All intentional ingredients are listed on the European EINECS Inventory.

SECTION 16 - OTHER INFORMATION

Revisional Updates

4/26/2019 - Updated Section 1.4 8/14/2015 - Updated Sections 14.1, 14.2, 14.3 and 14.4 5/29/2015 - Updated Sections 2.1 and 3.2 9/17/2013 - Released Version 1.0

NFPA Codes

Health 1 Flammability 1 Reactivity 0

Dangers

Phenyl Xylyl Ethane (PXE)

H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Primary Alcohol Ethoxylate

H318 - Causes serious eye damage.

Linear alkyl phenyl ethoxylates

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

Butoxy Ethanol

H302 - Harmful if swallowed

H312 - Harmful in contact with skin.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

MANUFACTURER DISCLAIMER: The information given herein is offered in good faith as accurate, but without guarantee. Conditions of the use and suitability of the product for particular uses are beyond our control. All risks of use of the product are therefore assumed by the user. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.